

2020-05-18  
300462358/pbsa56

## Security Advisory for Phoenix Contact FL NAT 2xxx

### Advisory Title

Users unauthorized by MAC based port security or 802.1x port security can get access to a routed subnet.

### Advisory ID

CVE-2019-18352  
VDE-2019-020

### Vulnerability Description

If MAC-based port security or 802.1x port security is enabled, the FL NAT 2xxx will unintentionally grant access to unauthorized devices in case of routed transmission.

```
Subnet 2---(Ports belonging to subnet 2)
          |
          FL NAT 2xxx
          |
          (Ports belonging to subnet 1, port sec ON)---- 2nd device
                                     |
                                     -- unauthorized device
```

The unauthorized device can access other devices in subnet 2 but cannot access the 2nd device in subnet 1

### Affected products

Article no.	Article	Affected Firmware	Current Firmware
2702882	FL NAT 2208	< 2.90	<a href="#">download</a>
2702981	FL NAT 2304-2GC-2SFP	< 2.90	<a href="#">download</a>

Personally liable partner:  
Phoenix Contact Verwaltungs GmbH  
Amtsgericht Lemgo HRB 5273  
Kom. Ges. Amtsgericht Lemgo HRA 3746Executive Vice Presidents:  
Frank Stührenberg (CEO)  
Roland Bent  
Prof. Dr. Gunther Olesch  
Axel WachholzDeutsche Bank AG  
(BLZ 360 700 50) 226 2665 00  
BIC: DEUTDE33XXX  
IBAN:  
DE93 3607 0050 0226 2665 00Commerzbank AG  
(BLZ 476 400 51) 226 0396 00  
BIC: COBADE33XXX  
IBAN:  
DE31 4764 0051 0226 0396 00

### **Impact**

If port security is enabled on a port, a device not authorized by MAC based port security or 802.1x based port security can access another subnet via the FL NAT 2xxx device that is routing between the subnet the unauthorized device is residing in and the 2<sup>nd</sup> subnet.

### **Classification of Vulnerability**

Base Score: 8.2

Vector: CVSS:3.0/AV:A/AC:L/PR:N/UI:N/S:C/C:N/I:H/A:L

### **Temporary Fix / Mitigation**

Users should take care that network security is not relying solely on separating subnets with MAC or 802.1x based port security if the FL NAT 2xxx device is serving as a router between the subnets.

**Update 2020-05-18:** Firmware V2.90 is released and available for download.

NOTE: If traps/logs/syslog for unauthorized access are enabled, notifications about the unauthorized access will be sent.

### **Acknowledgement**

This vulnerability was discovered during internal audits due to a customer complaint.